


ELEMENT 4NS WOOD FACIA

BY NATIONAL LIGHTING

DATE





CERTIFICATIONS / TERMS









AMERICAN ACT* ALL COMPONENTS SERVICEABLE *

TYPE


PROJECT

COMMENTS

DESCRIPTION

The ELEMENTis ideal for direct/indirect applications in open office areas, utilizing unfinished and open ceiling systems. The ELEMENT series is a perfect creative compliment to today's communal workplaces and tech ecosystems. The ELEMENT can be run in straight lines, right angles, rectangles and a myriad of shapes. The diffused, regressed LED light source works seamlessly with the natural, uncluttered work environments so prevelant in creative hubs today. The ELEMENT is the perfect light source to compliment the other equipment and furnishings in the space.

CROSS SECTION



1. HOUSING

To be formed from 20GA Aluminum Finish: Baked white enamel (standard) Direct / Indirect Lighting (standard) All fixtures pre-wired

All steel parts are phosphate treated for corrosion resistance before painting procedure and then baked with superior adhesion for durability

2 DRIVER

0-10V Dimming with a range of 10% - 100% (integral)
Voltage: 120/277 VOLTS (universal) 50/60HZ
CBM / ETL Certified CLASS 2 - Dual circuited
UL/ETL Recognized components, ROHS Compliant with integral occ sensor

3. LED ARRAY

Mid power FR4 LED LM80 Tested (Factory installed) LED imaging not visible Flicker free (standard)

4. REFLECTOR

To be formed from 20GA Aluminum Finish: White (standard)

5. DIFFUSER

.125" frosted acylic dropped lens

| | | | | | | | | | | ORDERING |
|---|---|---------------------|-----------------|--|------------------|--|----------------|---|---|-------------|
| SERIES | LENGTH* | OUTPUT* | RATIO D/ID | VOLTAGE | CCT | CRI - R9 | COLOR* | MOUNTING | OPTIONS | FINISH |
| ELEMENT 4NS WOOD | | | | UNV | | | | | | |
| | XXX FT 1'INCREMENTS STARTING AT 2' EX: 2' = 002 | 14W 1320 LM/FT | 10 100/00 | UNV 120-277 Volt | 27 2700K | 80+ 80 CRI R9 40 | W WHITE | AC AIRCRAFT CABLE | SD DIM 0-10V SC SIN | GLE CIRCUIT |
| | | 12W1135 LM/FT | 75 75/25 | | 30 3000K | 90+ 90 CRI B BLACK S SILVER *C CUSTOM PROVIDER | B BLACK | P STEM MOUNT | S1 DIM TO 1% 0-10V DC DU | AL CIRCUIT |
| | | 10W 945 LM/FT | 64 60/40 | | 35 3500K | | S SILVER | | L2 LUTRON 2-WIRE 1% DIM L3 LUTRON 3-WIRE 1% DIM | |
| | | 9W 850 LM/FT | 55 50/50 | | 40 4000K | | *C CUSTOM | | | |
| | | 7W 660 LM/FT | 46 40/60 | | 50 5000K | | PROVIDENAL | | DA DALI | |
| 27 25/7. | | | 27 25/75 | | TW TUNABLE WHITE | | | | OC OCCUPANCY SENSOR | |
| * 5 YEAR PERFORMANCE BASED WARRANTY CONSULT FACTORY FOR DETAILS 01 00/100 | | | | RGB COLORTU | INING | *OTHER FINISHES AVAILABLE - CONTACT FACTORY | | EN ENLIGHTED (INTEGRAL OR REMOTE) | | |
| * BUY AMERICA ACT COMPLIANT (2009 STANDARDS) * ALL INTERNAL PARTS ARE ACCESSABLE / SERVICEABLE (DRIVERS / LED BOARDS / QUICK CONNECTS) | | | | * ALL LENGTHS ARE NOMINAL * ALL LUMEN OUTPUT / WATTAGES ARE NOMINAL | | | | | EM EMERGENCY PACK | , |
| | | NIA. | TIONIAL LICITI | NIC COMMONNIN | FAA CODTLAN | DT CT DELLEV | ILLE NIL 07100 | 1 072 751 1600 \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ | / NIATITO COM | |